

Messing-Rundstangen Cu Zn 39 Pb 3 (Ms 58) CW 614 N

in HL von ca. 3 m

EN 12164/12165



Durchmesser mm	kg/mtr.	Durchmesser mm	kg/mtr.	Durchmesser mm	kg/mtr.	Durchmesser mm	kg/mtr.
2	0,03	15	1,50	35	8,17	105	73,56
3	0,06	15,5	1,60	36	8,65	110	80,74
4	0,11	16	1,71	37	9,13	120	96,08
5	0,17	17	1,93	38	9,64	130	112,77
5,5	0,20	18	2,16	40	10,68	140	130,78
6	0,24	19	2,41	42	11,77	150	150,13
6,5	0,28	20	2,67	45	13,51	160	170,82
7	0,33	21	2,94	48	15,37	170	192,84
7,5	0,38	22	3,23	50	16,68	180	216,19
8	0,43	23	3,53	55	20,18	190	240,88
8,5	0,48	24	3,84	60	24,02	200	266,90
9	0,54	25	4,17	65	28,19	220	322,95
10	0,67	26	4,51	70	32,70	225	337,80
10,5	0,74	27	4,86	75	37,53	250	417,03
11	0,81	28	5,23	80	42,70	260	451,06
12	0,96	30	6,01	85	48,21	280	523,12
12,5	1,04	32	6,83	90	54,05	300	600,53
13	1,13	33	7,27	95	60,22		
14	1,31	34	7,71	100	66,73		

Messing-Vierkantstangen Cu Zn 39 Pb 3 (Ms 58) CW 614 N

in HL von ca. 3 m

EN 12164/12165



Abmessung mm	kg/mtr.	Abmessung mm	kg/mtr.	Abmessung mm	kg/mtr.	Abmessung mm	kg/mtr.
5 x 5	0,21	14 x 14	1,67	30 x 30	7,65	60 x 60	30,60
6 x 6	0,31	15 x 15	1,91	35 x 35	10,41	65 x 65	35,91
7 x 7	0,42	16 x 16	2,18	40 x 40	13,60	70 x 70	41,65
8 x 8	0,54	20 x 20	3,40	45 x 45	17,21	80 x 80	54,40
10 x 10	0,85	25 x 25	5,31	50 x 50	21,25	100 x 100	85,00

Messing-Sechskantstangen Cu Zn 39 Pb 3 (Ms 58) CW 614 N

gez. bzw. gepr. in HL von ca. 3 m

EN 12164/12165



Abmessung SW / mm	kg/mtr.	Abmessung SW / mm	kg/mtr.	Abmessung SW / mm	kg/mtr.	Abmessung SW / mm	kg/mtr.
5	0,18	13	1,24	22	3,56	46	15,58
6	0,26	14	1,44	24	4,24	50	18,40
7	0,36	15	1,65	27	5,36	55	22,27
8	0,47	16	1,88	28	5,76		
9	0,60	17	2,12	30	6,62		
10	0,74	18	2,38	32	7,53		
11	0,89	19	2,65	36	9,53		
12	1,06	20	2,94	41	12,36		