



Kupferblech Cu-ETP CW 004 A/E-Cu/Cu-DHP CW 024 A/SF-Cu,
weich R 220 + halbhart R 240

EN 1652



Dicke mm	Abmessung 1000 x 2000 kg/Tfl.	Abmessung 1250 x 2500 kg/Tfl.	Dicke mm	Abmessung 1000 x 2000 kg/Tfl.	Abmessung 1250 x 2500 kg/Tfl.
0,5	8,9	–	3,0	53,4	83,4
0,6	10,7	–	4,0	71,2	–
0,7	12,5	–	5,0	89,0	–
0,8	14,2	–	6,0	106,8	–
0,9	16,0	–	8,0	142,4	–
1,0	17,8	27,8	10,0	178,0	–
1,2	21,4	–	15,0	267,0	–
1,5	26,7	41,7	20,0	356,0	–
2,0	35,6	55,6	25,0	445,0	–
2,5	44,5	–	30,0	534,0	–

Bänder bis 1000 mm Breite gespalten in allen Stärken

Stärke	Cu-ETP/E-Cu/Cu-DHP/SF-Cu		Stärke	Cu-ETP/E-Cu/Cu-DHP/SF-Cu	
	F 20	F 25		F 20	F 25
0,20	x	x	0,80	x	x
0,25	x	x	0,90	x	x
0,30	x	x	1,00	x	x
0,40	x	x	1,20	x	x
0,50	x	x	1,50	x	x
0,60	x	x	2,00	x	x
0,70	x	x	3,00	x	x

Bedachungsbleche – Alle kurzfristig lieferbar.